



Technique	Hand woven / Flat woven	ISO 2424
Finishing options	Binding uni, Folded sides, Top & end folded blind + selvages	
Application	Wall to wall, Area rug, Stairway runner	
Design	Custom colour	
Pile composition	75% Wool - 25% Polyamide	
Total weight	2000 gr/m <sup>2</sup>	ISO 8543
Total height	Wall to wall installation - 4.5 mm Finished rug - 8 mm	ISO 1765
Maximum width	500 cm	ISO 3018
Pattern repeat	11.5 cm	
Domestic use class	Class 23 / domestic heavy use	ISO 10361
Commercial use class	Class 33 / commercial heavy use	ISO 10361
Reaction to fire	Bfl-s1	ISO 9239-1
Abrasion resistance	Martindale: no thread breakage at 100,000 cycli	ISO 12947
Slip resistant	Yes	
Thermal resistance (R)	0,066 m <sup>2</sup> K/W / suitable for heated floors	ISO 8302
Other qualities	Impact noise reduction, Sound absorption, Permanently suitable for castor chairs	



### Application as wall-to-wall & stairway runner

For wall to wall installation we strongly recommend the use of an underlay.

For more information visit [www.bomat.eu/en/application](http://www.bomat.eu/en/application)

### Maintenance

Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company. More info: [www.bomat.eu/en/care-and-maintenance](http://www.bomat.eu/en/care-and-maintenance)



Blue Grey




Brown



Deep Red




Green




Grey




Lavender




Neutral




Red



Rust




Soft Blue



Vieux Rose

Pattern repeat  
11.5 cm border

11.5 cm



2.5 cm