



Technique	Hand woven / Cut- and loop pile	ISO 2424
Finishing options	Binding uni	
Application	Wall to wall, Area rug	
Design	Custom colour, Custom shape	
Pile composition	95% New Zealand Wool - 5% Cotton	
Total weight	4500 g/m²	ISO 8543
Total height	Wall to wall installation 14.5 mm Finished rug - 16.5 mm	ISO 1766
Maximum width	500 cm	ISO 3018
Pattern repeat	15 cm x 15 cm	
Domestic use class	Class 23 / domestic heavy use	ISO 10361
Commercial use class	Class 33 / commercial heavy use	ISO 10361
Reaction to fire	Bfl-s1	ISO 9239-1
Abrasion resistance	4 / change after 4000 rotations	ISO 24338
Slip resistant	Yes	
Thermal resistance (R)	0,2392 m².K/W	ISO 8302
Luxury class	Luxury Class 5	
Other qualities	Impact noise reduction, Sound absorption	



Application as wall-to-wall & stairway runner

For wall to wall installation we strongly recommend the use of an underlay.


For more information visit www.bomat.eu/en/application

Maintenance


Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company.

More info: www.bomat.eu/en/care-and-maintenance



Castle Wall




Fired Brick




Lava Stone




Lilac Ash




Limestone




Mossed Concrete



Polyfloor



Porcelain Tile



Warm Stone



Yellow Brick

Pattern repeat
15 cm x 15 cm

