



Technique	Hand woven / Flat woven	ISO 2424	
Finishing options	Binding uni, Fringes top & bottom + selvages, Top & end folded blind + selvages		  
Application	Wall to wall, Area rug, Stairway runner		  
Design	Custom colour, Custom shape		 
Pile composition	60% Wool - 20% Polyamide - 20% Hemp		
Total weight	2047 gr/m ²	ISO 8543	
Total height	Wall to wall installation - 6.5 mm Finished rug - 8-12 mm	ISO 1765	
Maximum width	450 cm	ISO 3018	
Pattern repeat	5 cm x 8.5 cm		
Domestic use class	Class 23 / domestic heavy use	ISO 10361	
Commercial use class	Class 33 / commercial heavy use	ISO 10361	
Reaction to fire	Cfl-s1	ISO 9239-1	
Abrasion resistance	Martindale: no thread breakage at 100,000 cycli	ISO 12947	
Slip resistant	Yes		
Thermal resistance (R)	0,066 m ² K/W / suitable for heated floors	ISO 8302	
Other qualities	Suitable for castor chairs, Impact noise reduction, Sound absorption,		  

Application as wall-to-wall & stairway runner

For wall to wall application we strongly recommend the use of an underlay.

For more information visit www.bomat.eu/en/application

Maintenance

Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company. More info: www.bomat.eu/en/care-and-maintenance


COLLECTION

Burghley




B O M A T


DEEP HUES · SOFT TEXTURES



Deep Orange




Dusty Lime



Misty Lilac



Soft Walnut



Warm Red

Pattern repeat
5 cm x 8.5 cm

