



Technique	Hand woven / Cut pile	ISO 2424	
Finishing options	Binding uni		
Application	Wall to wall, Area rug		
Design	Custom colour, Custom shape		
Pile composition	95% New Zealand Wool - 5% Cotton		
Total weight	4000 g/m ²	ISO 8543	
Total height	Wall to wall installation - 12 mm / 15 mm Finished rug - 14 mm / 17 mm	ISO 1766	
Maximum width	500 cm	ISO 3018	
Pattern repeat	7 cm x 19 cm		
Domestic use class	Class 22 / domestic general use	ISO 10361	
Commercial use class	Class 31 / commercial light use	ISO 10361	
Reaction to fire	Bfl-s1	ISO 9239-1	
Abrasion resistance	3,5 / change after 4000 rotations	ISO 24338	
Slip resistant	Yes		
Thermal resistance (R)	0,2392 m ² .K/W	ISO 8302	
Luxury class	Luxury Class 4		
Other qualities	Impact noise reduction, Sound absorption		

Application as wall-to-wall & stairway runner


For wall to wall installation we strongly recommend the use of an underlay.

For more information visit www.bomat.eu/en/application


Maintenance

Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company. More info: www.bomat.eu/en/care-and-maintenance




Burnt Brick




Castle Wall



Lilac Ash



Mossed Concrete



Warm Stone



Yellow Brick

Pattern repeat
7 cm x 19 cm

