



Technique	Hand woven / Cut- and loop pile	ISO 2424
Finishing options	Binding uni	
Application	Wall to wall, Area rug	
Design	Custom colour, Custom shape	
Pile composition	95% New Zealand Wool - 5% Cotton	
Total weight	4500 g/m <sup>2</sup>	ISO 8543
Total height	Wall to wall installation - 14 mm Finished rug - 16 mm	ISO 1766
Maximum width	400 cm	ISO 3018
Pattern repeat	6 cm x 6 cm	
Domestic use class	Class 23 / domestic heavy use	ISO 10361
Commercial use class	Class 33 / commercial heavy use	ISO 10361
Reaction to fire	Bfl-s1	ISO 9239-1
Abrasion resistance	4 / change after 4000 rotations	ISO 24338
Slip resistant	Yes	
Thermal resistance (R)	0,1906 m <sup>2</sup> .K/W	ISO 8302
Luxury class	Luxury Class 4	
Other qualities	Impact noise reduction, Sound absorption	



### Application as wall-to-wall & stairway runner

For wall to wall installation we strongly recommend the use of an underlay.


For more information visit [www.bomat.eu/en/application](http://www.bomat.eu/en/application)

### Maintenance


Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company.

More info: [www.bomat.eu/en/care-and-maintenance](http://www.bomat.eu/en/care-and-maintenance)



Castle Wall



Polyfloor

---

**Pattern repeat**  
6 cm x 6 cm

