



Technique	Hand woven / Low loop pile	ISO 2424
Finishing options	Binding uni	
Application	Wall to wall, Area rug	
Design	Custom colour, Custom shape	
Pile composition	60% New Zealand Wool - 20% Cotton - 20% Polyamide	
Total weight	3019 gr/m ²	ISO 8543
Total height	Wall to wall installation - 5.5 mm Finished rug - 8 mm	ISO 1766
Maximum width	460 cm	ISO 3018
Pattern repeat	All-over pattern	
Domestic use class	Class 23 / domestic heavy use	ISO 10361
Commercial use class	Class 32 / commercial general use	ISO 10361
Reaction to fire	Cfl-s1	ISO 11925-2
Abrasion resistance	4-5 / change after 4000 cycli	ISO 24338
Slip resistant	Yes	
Thermal resistance (R)	0.0677 m ² K/W / suitable for heated floors	ISO 8302
Luxury class	Luxury Class 1	
Other qualities	Impact noise reduction, Sound absorption, Lightfastness, Permanently suitable for castor chairs	



Application as wall-to-wall & stairway runner

For wall to wall installation we strongly recommend the use of an underlay.

For more information visit www.bomat.eu/en/application

Maintenance

Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company.

More info: www.bomat.eu/en/care-and-maintenance


COLLECTION

Mapuche



B O M A T


DEEP HUES · SOFT TEXTURES




Black



Dove




Dusk




Sahara




Snow



Sparrow



Terre Cuite



Wood Ash

Pattern repeat
Plain

