



Technique	Hand tufted / Cut pile	ISO 2424
Finishing options	Binding uni	
Application	Wall to wall, Area rug, Stairway runner	
Design	Custom colour, Custom shape, Proposed organic shapes	
Pile composition	90% New Zealand Wool - 10% Cotton	
Total weight	3500 gr/m ²	ISO 8543
Total height	Wall to wall installation - 14 mm Finished rug - 16.5 mm	ISO 1766
Maximum width	500 cm	ISO 3018
Pattern repeat	Plain	
Domestic use class	Class 23 / domestic heavy use	ISO 10361
Commercial use class	Class 32 / commercial general use	ISO 10361
Reaction to fire	Bfl-s1	ISO 11925-2
Abrasion resistance	3 / change after 4000 cycli	ISO 24338
Slip resistant	Yes	
Thermal resistance (R)	0,2392 m ² .K/W	ISO 8302
Luxury class	Luxury Class 3	
Other qualities	Impact noise reduction, Sound absorption, Lightfastness	



Application as wall-to-wall & stairway runner

For wall to wall application we strongly recommend the use of an underlay.

For more information visit www.bomat.eu/en/application

Maintenance


Regular vacuuming is indispensable for the maintenance of any kind of carpet. Prerequisite for a successful removal of stains is the identification of the stain type and the correct approach. The sooner a stain is treated, the easier it is to remove.

We advise you to use a professional carpet cleaning company.

More info: www.bomat.eu/en/care-and-maintenance



Blanc



Brun



Ebony



Greige



Pesto

Pattern repeat
Plain

